

# Produktdatenblatt




## Higo - S828A

Female panel mount connector, self-locking



S828AM C 03 FN 0300

<https://www.higoconnector.ac-solutions.be/de/e-bike-steckverbinder/s828amc03fn0300>



## Spezifikationen

### General Characteristics

|                               |                                    |
|-------------------------------|------------------------------------|
| x_number_of_contacts_detailed | 8 (2+2+4)                          |
| x_connector_shape_detail      | Panel mount                        |
| x_gender_detailed             | Female                             |
| x_color                       | Black                              |
| x_upper_temperature           | 80 °C                              |
| x_lower_temperature           | -25 °C                             |
| x_protection_degree           | IP67                               |
| x_mating_cycles               | 3000 Times                         |
| x_connector_diameter          | 28,5 mm                            |
| x_cable_length                | 300 mm                             |
| x_wire_section                | 2 x 2,5 + 2 x 1,3 + 4 x 0,2        |
| x_remark                      | Other cable length/type on request |

# Produktdatenblatt

## Higo - S828A

Female panel mount connector, self-locking



### Electrical Parameters

|                          |                   |
|--------------------------|-------------------|
| xRatedCurrent            | 25 / 10 / 2 A     |
| xRatedVoltage            | 48 V AC / 60 V DC |
| xMaxInsulationResistance | ?20 M?            |
| xMaxContactResistance    | ?10 m?            |

### Material

|                    |                  |
|--------------------|------------------|
| xMaterialOfContact | Phosphor Bronze  |
| xContactPlating    | Gold over Nickel |